

TYRE INFLATION & AIR EQUIPMENT

Air Equipment Tyre Inflation	436
Air Equipment Tyre Gauges	438
Air Equipment Chucks Non-Sealing	439
Air Equipment Chucks Sealing	439
Gas Equipment Adaptors.	440
Air Equipment Tyre Equipment	441
Air Equipment Tyre Accessories.	441
Air Equipment Airline Fittings Tailpiece	442
Air Equipment Hose Reels Pro Series Retractable	444
Air Equipment Hose Reels Multi-Purpose.	446
Air Equipment Hose Reels Oxy/Acetylene	446
Hose Reels Hose Reels Pro Series Extreme Retractable	447
Air Equipment Blow Guns	447

JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

TDR 2000 TYRE INFLATOR



FEATURES:

- Die cast aluminium body with steel operating lever and impact absorbing bumper
- Supplied with official calibration certificate
- Laser etched serial number for individual I.D.
- Colour co-ordinated bumper and face plate
- Ideal for service station forecourts
- Wire sheathed hose eliminates kinking
- Accuracy exceeds EC Directive 86/217
- Rubber grip on chuck

Specifications	
Reader Unit	Linear with magnifying glass
Chuck Type	Hold on
Chuck Style	Dual angle
Scale	0-138 p.s.i., 0-960 kpa
Inlet Size	1/4 " BSP female
Hose Length	500 mm
Dimensions	265 L x 50 W mm
Weight	.95 kg
Accuracy*	± 2 p.s.i. @ 25-75 p.s.i.
Operation	Inflate, Deflate, Measure
Supply Pressure Max.	200 p.s.i
Advised Application	Industrial, Workshops
Inflation Volume	500 L/min @ 188 p.s.i.
Item No.	JP10.2000
Barcode	9318728012306

TDR DIGITAL TYRE INFLATOR



FEATURES:

- Includes certificate of calibration
- Accuracy exceeds EC Standards
- Multi-scale gauge
- Serial / batch numbered
- Backlit display
- Wire sheathed hose eliminates kinking
- Impact absorbing bumpers
- Rubber grip on chuck
- Tough die cast aluminium body
- Packaged in colour display box

Specifications	
Reader Unit	Digital with backlit display
Chuck Type	Hold on
Chuck Style	Dual angle
Scale	0-174 p.s.i., 0-1200 kPa, 0-12 bar
Inlet Size	1/4 " BSP female
Hose Length	500 mm
Dimensions	265 L x 50 W x 70 H mm + hose + chuck
Weight	.95 kg
Accuracy	± 2 p.s.i. @ 25 - 75 p.s.i.
Operation	Inflate, deflate, measure
Supply Pressure Max.	200 p.s.i.
Max. Inflation	174 p.s.i.
Powered By	2 x AAA (included)
Battery Life (Continuous Use)	80 hr
Inflation Volume	500 L/min @ 188 p.s.i.
Notes	Auto ON once pressure is sensed or air inflation takes place/ Auto OFF (8 seconds)
Advised Application	Industrial, workshops
Item No.	JP10.3100
Barcode	9312652084859

DIGITAL AUTOMATIC TYRE INFLATOR



FEATURES:

- Includes certificate of calibration
- Accuracy exceeds EC Directive 861217
- Multi-scale gauge
- Serial / batch numbered
- Backlit display
- Includes Nitto equivalent adaptor
- Tough die cast aluminium body
- OPS (Over Pressure Setting) function that allows the tyre to be inflated to a certain pressure then deflates automatically to a normal operating pressure, used for seating tyres on rims.
- Mechanical anti-vandal buttons
- Comprehensive diagnostics and error reporting
- Inflates accurately with hoses up to 50 m long (I.D. size should be considered when used with a long hose)

Specifications

Reader Unit	Digital with backlit display with audible warning
Chuck Type	Clip on
Chuck Style	Single straight
Scale	174 p.s.i., 1200 kPa, 12 bar, 0-12 kg/cm ²
Inlet Size	1/4 " BSP female
Hose Length	7.5m
Dimensions	230 L x 278 W x 85 H mm
Weight	5.5 kg
Accuracy	± 3 p.s.i. @ 25 - 75 p.s.i.
Operation	auto inflate, auto deflate, measure
Supply Pressure Max.	182 p.s.i
Max. Inflation	174 p.s.i.
Powered By	240 V AC
Inflation Volume Litres P/M	3,000 L/min @ 182 p.s.i.,
Ip Rated	56
Advised Application	Forecourt, industrial, workshop
Item No.	JP11.0545
Barcode	9312652040282



DIAL GAUGE WITH TREAD DEPTH INDICATOR

FEATURES:

- This quality tyre gauge utilises internal diaphragm technology, ensuring accuracy and reliability
- Dual scale:
 - 2 p.s.i. increments up to 70 p.s.i.
 - 20 kPa increments up to 500 kPa
- Angled hold on chuck
- Protective rubber cover
- Tread depth indicator - 11 mm
- Shock resistant - diaphragm internal mechanism
- Industrial quality
- Hang sell blister pack

Specifications	
Reader Unit	50 mm dial gauge
Chuck Type	Hold on
Chuck Style	Single angle
Scale	10 - 70 p.s.i., 100 - 500 kPa
Dimensions	115 L x 50 W x 32H mm
Weight	30 kg
Accuracy	± 2 p.s.i. @ 25 - 75 p.s.i.
Item No.	JP05.3078
Barcode	9312652083258




TRACTOR TYRE GAUGE

FEATURES:

- Ideal for tyre fitters and heavy trade
- Stainless steel spring with aluminium read bar
- Pocket clip
- Can be used with water filled tyres
- Hang sell blister pack



Specifications	
Reader Unit	Sliding bar
Chuck Type	Hold on
Chuck Style	Single angle
Scale	0 - 50 p.s.i., 0 - 350 kPa
Dimensions	150 L mm
Weight	06 kg
Accuracy	± 2 p.s.i. @ 25 - 75 p.s.i.
Operation	Hold on/read
Advised Application	Industrial, tractor, home
Item No.	JP05.2875
Barcode	9318728000532



STRAIGHT LARGE BORE CLIP ON CHUCK

FEATURES:

- Non-sealing
- Large bore head suitable for earth moving equipment

Specifications	
Chuck Type	Clip on
Chuck Style	Single straight large bore
Operation	Non sealing
Tail/Thread Type	Female
Tail/Thread Size	1/4 " BSP female
Dimensions	45 L mm
Weight	.10 kg
Item No.	JP03.0497
Barcode	9312652001528



DUAL ANGLE HOLD ON CHUCK - SEALING

FEATURES:

- Rubber grip

Specifications	
Chuck Type	Hold on
Chuck Style	Dual angle
Operation	Sealing
Tail/Thread Type	Female
Tail/Thread Size	1/4 " BSP female
Dimensions	24 L cm
Weight	.14 kg
Item No.	JP03.0472
Barcode	9318728013310



TYRE VALVE CONNECTOR SERVICE KIT

FEATURES:

- Service Kit for Twin Hold-on (Closed End) Connector JP03.0472

Item No.	JP10.2268
Barcode	5014875790107



HOSE JOINER SUITS 5MM ID HOSE SCREW FITTING

FEATURES:

- Solid brass construction

Specifications	
Use With	5mm ID hose
Weight	0.1kg
Item No.	JP228189
Barcode	9312652090966



HOSE REGULATOR CONNECTION KIT SUITS 5MM ID OXYGEN HOSE

FEATURES:

- Solid brass construction

Specifications	
Use With	5mm ID hose
Weight	0.1kg
Thread	5/8" – 18 UNF RH thread to screw directly onto oxygen regulator
Item No.	JP228201
Barcode	9312652090973




HOSE REGULATOR CONNECTION KIT SUITS 5MM ID ACETYLENE OR LPG HOSE

FEATURES:

- Solid brass construction

Specifications	
Use With	5mm ID oxygen hose
Weight	0.1kg
Thread	5/8" – 18 UNF LH thread to screw directly onto acetylene or LPG regulator
Item No.	JP228212
Barcode	29312652090980



PRIMUS TO 3/8" ADAPTOR

FEATURES:

- High quality brass adaptor
- Adjustable On/Off and variable control valve
- Thread (in): Primus male
- Thread (out): 3/8" BSP LH male

Specifications	
Item No.	JPPRI01
Barcode	9317200001159



TYRE VALVE REPAIR TOOL

FEATURES:

- Blister packed
- Tyre valve repair tool removes the core and re-threads the valve case
- Small bore valve cores

Item No.	JP32.2501
Barcode	9318728500032



TYRE TREAD DEPTH GAUGE

FEATURES:

- Metric: 0 - 25 mm, Imperial: 0/32 - 32/32 " scale
- Dual scale
- Blister packed

Item No.	JP32.2556
Barcode	9312652039668



TANK VALVE

FEATURES:

- Short 1/8 " BSP male
- Pack lots of 5

Item No.	JP32.3077
Barcode	9318728003472

Air Equipment Tyre Accessories



TWIN CLIP ON CONNECTOR OPEN END

FEATURES:

- Tyre Valve Connection: Twin clip-on
- Valve Style: Open End
- Inlet Size: Rp 1/4
- Suitable for inflation of twin tyres
- Clip on feature allows user space from tyre
- Suitable for tyre shop use
- Colour coded handle (Black - Open End)

Item No.	JP03.0470NZ
Barcode	9317200018331



SINGLE FOOTPUMP

FEATURES:

- All steel construction for added strength
- Anti-corrosive finish
- Barrel pressure sealed to prevent leakage
- Easy to read dial gauge
- Adaptors for airbed, cycle valves and footballs provided
- Sturdy anti-slip pedal and rubber feet

Calibration	0-100 lbf/in ² & 0-7 bar
Item No.	JP11.2025
Barcode	5014875310190

LONG VALVE CORES

FEATURES:

- Supplied in packet of 4
- Long tyre valve cores suitable for standard tyre valves
- Resistant to petrol, oil and other contaminants

Item No.	JP32.3091
Barcode	5014875200019

TYRE VALVE EXTENSION 19MM



FEATURES:

- Supplied in packet of 4
- Plastic tyre valve extensions allow for easier access to the valve

Item No.	JP32.3093
Barcode	5014875200057



TAILPIECES MALE WITH BARBED ENDS



FEATURES:

- Heavy duty industrial strength
- Long lasting brass

Specifications	
Archive Item No.	8TM4
Tail/Thread Type	12.5 mm, 1/2 "
Tail/Thread Size	1/4 " BSP
Item No.	JP28.1209
Barcode	9318728002727

EURO ADAPTOR 1/4" MALE



FEATURES:

- For use with Euro couplings
- Steel construction with corrosive resistant finish
- Suitable for general compressed air applications

Specifications

Thread Type	Male
Thread Size	R 1/4
Item No.	JP59.3350
Barcode	5014875360287

EURO ADAPTOR 1/4" FEMALE



Specifications

Thread Type	Female
Thread Size	R 1/4
Item No.	JP59.3351
Barcode	5014875360270

EURO ADAPTOR 9.5MM (3/8") HOSE TAILPIECE



Specifications

Thread Type	Hose Tailpiece
Thread Size	9.5mm (3/8")
Item No.	JP59.3353
Barcode	5014875360317



With the unique HELIX Ultra-Coil self layering hose system, combined with a precision machined solid brass central spindle, the Jamec Pem Pro Series hose reels are ideally suited for the trade or industrial workshop.

- High impact tough and durable polypropylene construction
- Fully enclosed weather resistant and UV stabilized outer case protects the hose and inner drum assembly against dirt and other contaminants
- Auto lock and rewind mechanism provides positive hose latching every full revolution of the hose drum
- 2 metre length leader hose with quality brass fittings included as standard
- Heavy duty mounting bracket with fixed in-line or optional 180 degree swivel mount is suitable for wall or overhead mounting
- Convenient carry handle located on the top panel for removing and refitting the hose reel from the mounting bracket
- Adjustable hose stopper
- Includes wall mounting bracket
- Brass fittings

RETRACTABLE HOSE REEL AIR 15 METRE



**PRO
SERIES
15 AIR**

Specifications	
Hose Length	15 m
Hose I.D.	12.5 mm, 1/2 "
Hose O.D.	18.5 mm, 3/4 "
Leader Hose Length	2 m with 3/8 " BSP male fitting
Hose Material	Reinforced PVC braided
Reel/Case Type	Retractable/polypropylene
Auto Lock/Auto Rewind	Yes
Max. Working Pressure	300 p.s.i., 2068 kPa
Fitting Size	3/8 " BSP male with swivel
Bracket	180° Pivoting
Weight	8.0 kg
Case Dimensions	440 L x 210 W x 400 H mm
Application	Air (High volume)
Item No.	JP58.1056
Barcode	9312652036285

RETRACTABLE HOSE REEL AIR 20 METRE



**PRO
SERIES
20 AIR**

Specifications	
Hose Length	20 m
Hose I.D.	9.5 mm, 3/8 "
Hose O.D.	16 mm, 5/8 "
Leader Hose Length	2 m with 1/4 " BSP male fitting
Hose Material	Reinforced PVC braided
Reel/Case Type	Retractable/polypropylene
Auto Lock/Auto Rewind	Yes
Max. Working Pressure	300 p.s.i., 2068 kPa
Fitting Size	1/4 " BSP male brass swivel
Bracket	180° Pivoting
Weight	8.0 kg
Case Dimensions	440 L x 210 W x 400 H mm
Application	Air
Item No.	JP58.1034
Barcode	9312652036261



RETRACTABLE HOSE REEL AIR 32 METRE

**PRO
SERIES
32 AIR**

Specifications	
Hose Length	32 m
Hose I.D.	8 mm, 5/16 "
Hose O.D.	12 mm, 1/2 "
Leader Hose Length	2 m with 1/4 " BSP male
Hose Material	Reinforced PU braided
Reel/Case Type	Retractable/polypropylene
Auto Lock/Auto Rewind	Yes
Max. Working Pressure	250 p.s.i., 1725 kPa
Fitting Size	1/4 " BSP male with swivel
Bracket	180° Pivoting
Weight	8.0 kg
Case Dimensions	440 L x 210 W x 400 H mm
Application	Air
Item No.	JP58.2012
Barcode	9312652045850



RETRACTABLE HOSE REEL WATER 20 METRE

- Fitted with Brass fittings and trigger nozzle

**PRO
SERIES
20**

Specifications	
Hose Length	20 m
Hose I.D.	11.5 mm, 1/2 "
Hose O.D.	16 mm, 5/8 "
Leader Hose Length	2 m with brass tap female fitting
Hose Material	Reinforced PVC braided
Reel/Case Type	Retractable/polypropylene
Auto Lock/Auto Rewind	Yes
Max. Working Pressure	150 p.s.i., 1034 kPa
Fitting Size	Brass tap fitting with water trigger dispenser
Bracket	180° Pivoting
Weight	8.0 kg
Case Dimensions	440 L x 210 W x 400 H mm
Application	Water
Item No.	JP58.1045
Barcode	9312652036278

Air Equipment Hose Reels Multi Purpose

JAMEC PEM
COUPLE UP WITH THE RIGHT CONNECTION

MULTI PURPOSE HOSE REEL



FEATURES:

- Can carry up to 20 m of PVC 10 mm (3/8") air hose or 40 m of PU 8 mm (5/16") air hose
- Nylon axle bushes for easy rewind
- Swivel base & swivel air input
- Brass fittings
- Sturdy steel construction
- Folding handle
- Ideal for air or water hose, chain, electrical leads
- Ideal for fixed or portable applications
- Hose guide to stop kinking on the inside of the reel

Specifications	
Fitting Inlet	1/4" BSP swivel
Fitting Outlet	1/4" BSP male to 10 mm (3/8") barbed ends
Capacity	Up to 40 m of PU 8 mm (5/16") air hose or 20 m 10 mm (3/8") air hose
Working Pressure	250 p.s.i.
Reel Type	Metal frame with swivel base
Frame	Tube steel
Handle	Folding metal with nylon handle
Axle Type	Metal with nylon axle bushes
Item No.	JP58.2078
Barcode	9317200002538

MULTI PURPOSE HEAVY DUTY METAL HOSE REEL



FEATURES:

- Can carry up to 70m of PVC 10mm (3/8") air hose or up to 60m of 12mm (1/2") water hose
- Nylon axle bushes for easy rewind
- Brass fittings
- Swivel air hose input
- Heavy duty box steel construction
- Folding handle
- Ideal for air or water hose, chain or electrical leads
- Ideal for fixed or portable applications
- Pre drilled mounting points
- Hose guide to stop hose kink on the inside of the reel

Specifications	
Fitting Inlet	1/2" BSP swivel with 10mm (3/8") barbed end
Fitting Outlet	1/2" BSP male to 10mm (3/8") barbed end
Capacity	Up to 70m of pvc 10mm (3/8") or 60m 12mm (1/2")
Working Pressure	300psi
Reel Type	Metal frame with roll over cage
Frame	20mm box steel
Handle	Folding metal with nylon handle
Mounting Points	Yes
Axle Type	Metal with nylon bushes
Item No.	JP58.2067
Barcode	9317200002521

MOUNT KIT TO SUIT HELIX REELS

Item No.	JP58.1078
-----------------	-----------

Air Equipment Hose Reels Oxy/Acetylene

OXY/ACETYLENE TWIN HOSE REEL



FEATURES:

- Suitable for all home handyman and trade applications.
- High impact industrial plastic case
- Quality brass fittings
- Self-retracting hose with click lock mechanism
- Detachable 180° swivel wall mount bracket
- Adjustable hose stopper
- Hose conforms to safety standard AS1335
- Note: All OXY/ACET systems must be fitted with Flashback Arrestors at both the cylinder and blowpipe handle ends.

Specifications	
Hose I.d	5mm
Hose O.D	10.5mm
Working Pressure	1.2mPa (max)
Lender Hose Length	2m
Hose Length	10m
Dimensions	420L x 230W x 390Hmm
Weight	7.50kg
Item No.	JP228523
Barcode	

PRO SERIES EXTREME AIR HOSE REEL

FEATURES:

- Auto lock / auto rewind
- Hose layering system
- Brass fittings
- High impact tough and durable polypropylene construction with a UV stabilised case
- 180° swivel wall mount bracket
- Leader hose 1 m with brass fittings
- Adjustable hose stop



Specifications	
Hose Length	8 m
Hose I.D.	9.2 mm
Hose O.D.	15.2 mm
Leader Hose Length	1 m with 1/4 " BSP male brass fitting
Hose Material	Extreme Ultraflex Reinforced Hose
Reel Case/Type	Retractable/Polypropylene
Auto Lock/ Auto Rewind	Yes
Max. Working Pressure	300 p.s.i.
Fitting Size	1/4 " BSP male brass fittings
Bracket	180° pivoting
Weight	4 kg
Dimensions	360 L x 330 W x 220 H mm
Application	Air
Item No.	JP58.3067
Barcode	9312652089090

Air Equipment Blow Guns

JAMEC PEM
COUPLE UP WITH THE **RIGHT** CONNECTION

AIR MASTER PISTOL GRIP EXTENDED

FEATURES:

- Brass insert in air inlet, brass valve
- Stainless steel spring
- Long reach 450 mm
- Hanging facility
- Hang sell blister pack



Specifications	
Grip Type	Pistol
Nozzle Type	450 mm with angle tip
Inlet Thread	1/4 " BSP female
Interchangeable Nozzle	Yes
Item No.	JP07.0774
Barcode	9318728001072

AIR MASTER PISTOL GRIP BLOW GUN

FEATURES:

- 85 mm nozzle, adjustable 360°
- Brass insert in air inlet, brass valve
- Stainless steel spring
- Variable trigger
- Hanging facility and controlled air flow
- Ergonomically designed for comfort during long intervals of use
- Hang sell blister pack



Specifications	
Grip Type	Pistol
Nozzle Type	85 mm with angle tip
Inlet Thread	1/4 " BSP female
Interchangeable Nozzle	Yes
Item No.	JP07.0770
Barcode	9318728001034